



FLYER[®] 72 |

HD HEAVY DUTY

STV

GROUP



The Flyer[®] 72 - Heavy Duty (F72-HD) ground mobility vehicle is a non-developmental item, purpose-built, lightweight vehicle designed to meet complex mission sets. Selected by the U.S. Special Operations Command (USSOCOM) as the vehicle of choice for their Ground Mobility 1.1 (GMV 1.1) program, at 72" wide it is capable of internal transport in the CH-47 and C-130 aircraft.

The F72-HD is a mature, highly mobile platform, with a payload capacity over 5,500 pounds, that can be configured to multiple crew sizes (up to nine). It can be guns up in less than one minute after exiting the aircraft, and is capable of carrying a variety of armaments. Its adaptable communications suite provides increased operating range and provides the operator real-time access to critical information.

As a reliable, high performance vehicle, the F72-HD offers safe and fast operating speeds with superior levels of mobility and maneuverability. It's highly adaptable to severe, rugged and restrictive terrains while providing off-road, cross-country mobility in all types of weather conditions.

- ◆ **Increased Speed, Mobility & Transportability**
- ◆ **Tailorable Command & Control Suite**
- ◆ **Scalable Modular Armor for Increased Protection**
- ◆ **Multiple Weapon Configurations**
- ◆ **Payload Adaptability**

Flyer Defense, LLC
151 W 135th St
Los Angeles, CA 90061

office: (310) 324-5650
fax: (310) 324-5646
flyerdefense.com

DRIVEN TO EXCEED™

FLYER 72-HD

PERFORMANCE

Top Speed	95 mph (153 kph)
Cruising Range	300 miles (483 km) at Mission Profile; 500 miles on flat ground at 40 mph (1,046 km)
Maximum Grade	60%
Dynamic Side Slope	40%
Fording	30" no prep (76 cm)



DIMENSIONS

Seating	Up to 5 seats: 3 front, 2 rear, with 5 point seat restraints
Wheelbase	126" (320 cm)
Length	182" (462 cm); 193" (490 cm) with pushbar and winch
Body Width	Chassis width: 72" Width at tire: 79.25" (201 cm) Width with side cargo box: 85" (216 cm)
Height	72" (183 cm) Adjustable
Curb Weight	7300 lb. (3311 kg)
Payload	5700 lb. (2585 kg)
Gross Vehicle Weight	13,000 lb. (5897 kg)
Approach Angle	73.4°/55.5° w/pushbar & winch
Departure Angle	53.1°
Ramp Over Angle	146.7°
Vertical Step	18" (45.7 cm)
Ground Clearance	14" (35 cm)
Fuel Capacity	23 gal. (87.5 L)
Chassis	Tubular Space Frame
Roll Cage	Integrated roll cages meets FMVSS 216 & SAE J2422 CH#5 & 6

POWERTRAIN

Engine Type	2.0 L GM DOHC BiTurbocharged Intercooled JP8/F24/Diesel Direct Injection Common Rail Fuel System
Horsepower/Torque	220 HP (164 kW)/ 332 ft. -lb. (450 Nm)
Transmission Type	Automatic power shift 6 speed (Tiptronic)
Torque Converter	Lockable
Differentials	Limited slip-front and limited-slip locking rear
Transfer Case	2 speed, high 4x2 or low full time 4x4

SUB SYSTEMS

HD Suspension, f/r	4-wheel coil over shocks independent adjustable suspension with 4 air spring variable ride
Service Brakes, f/r	Power assist 4-wheel disc with ABS
Wheel and Tire Size	Wheel size 37 x 13.5 R17 load range E with bead lock and VFI run flat

ELECTRICAL

12V Alternator	12V, 140 amp
12V/28V Alternator	12V/28V, 50/210 amp

MISSION CONFIGURATION - KITS

Weapons Compatibility	Remote Weapon System (RWS) 9 Javelin capacity: 6 in rear deck, 2 in roof racks, 1 loaded in RWS 4 M72-LAW stowed: 2 on roof racks, 2 inside on rear curtain
-----------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------



Trademark and Copyright Notice
©2022 Flyer Next, LLC and Flyer Defense, LLC - All Rights Reserved

All trademarks are registered or unregistered trademarks of Flyer Next, LLC, Flyer Defense, LLC or one of their affiliates in the U.S. and are protected under trademark laws of the United States and certain foreign jurisdictions. Trademarks of third parties may appear in this presentation to refer to those companies' goods and services and are the property of their respective owners.

